

P

proline

decorative concrete
systems



Measure and mix with water.



Agitate



Apply with EZ-Tique brush
and let dry thoroughly



•Use on new and existing concrete.

•Apply using different colors at the same time.

•Available in over 40 colors. Custom colors available.

proline

For more information please contact us at:

1-800-795-4750

www.prolinestamps.com

DESCRIPTION: PROLINE Duracolor **EZ-TIQUE™** is a cementitious antiquing wash that can be easily applied and will hold fast to any textured concrete surface. **EZ-TIQUE™** is sold as a powder that is designed to be mixed with water and applied as a liquid wash coat. **EZ-TIQUE™** can be used to revitalize a weathered concrete surface or add an antique color to a freshly textured surface. It goes on quickly and easily and can be removed readily for greater control of the coloring process. This product is water-based, not hazardous, and zero VOC. It comes in 42 standard colors, matching the PROLINE Duracolor CH and AR Color Chart, and custom colors can be matched.

APPLICATION: ☒ NOW SPRAYABLE ☒ PROLINE **EZ-TIQUE™** is intended for professional use only. It comes in a one gallon pail with 3 pounds of colored powder in a plastic bag, and a measuring cup. To mix, remove the plastic bag from the pail, fill the pail with water, and mix in one full measuring cup of the powder. Use more or less of the powder in one gallon of water to achieve different results in color intensity. **EZ-TIQUE™** can be mixed easily with a stir stick so motorized mixing is not necessary, but the product in the pail will need to be agitated periodically during application to keep the solids from settling. The settling property of **EZ-TIQUE™** is important in reaching the desired antique effect. Before applying the product to unsealed concrete, it is helpful to pre-moisten the surface with water so the liquid color will have time to even out and settle properly. The most basic technique to apply **EZ-TIQUE™** is to use a Proline **EZ-TIQUE™** brush, making sure to leave a uniform coat of liquid over the area to be covered. Be sure to have clean water handy to spray on the surface to make sure the color spreads uniformly. **EZ-TIQUE™** can also be sprayed on with a simple pump type sprayer. **EZ-TIQUE™** is easily cleaned up with water while it is still wet and can be wiped off with a clean dry sponge when dry.

COVERAGE: One 3 pound bucket of PROLINE **EZ-TIQUE™** covers 2000-3000 square feet.

STORAGE: Store in a cool, dry place in temperatures below 120°F. Shelf life is approximately one year, but can be much longer if containers are kept tightly sealed.

WARRANTY: This product is warranted to be of uniform quality within reasonable manufacturing tolerances. The manufacturer has no control over the use of the product, therefore, no warranty, express or implied, is or can be made either as to the effects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's appropriate applicability and assumes all risk and liability. We always recommend testing the product in an inconspicuous area to determine if the results will meet your expectations.

WARNING: THIS PRODUCT MAY CONTAIN A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. Avoid contact with eyes and skin. Wear gloves to protect skin and safety goggles to protect eyes. Before using this product completely read the EZ-Tique Technical Data Sheet and SDS. **KEEP OUT OF REACH OF CHILDREN.**

PROLINE DECORATIVE CONCRETE SYSTEMS
2664 VISTA PACIFIC DR OCEANSIDE, CA, 92056
800-795-4750
PROUDLY MADE IN THE USA